



FGDB Pump Machinery Equipment Co., Ltd.

4SRS12M+[36-1000/1]LM THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. 4SRS12M+[36-1000/1]LM

Days to Ship	3 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	4
Nominal Part Number	12
Rail Type	Standard
Rail Width W1	12 mm
Mounting Height M	13 mm
Rail Length L	36 ~ 1000 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	4000
Basic Load Rating Static Rating Co(N)	3530
Allowable Static Moment MA(N m)	12
Allowable Static Moment MB(N m)	12
Allowable Static Moment MC(N m)	23.1
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	27 mm
Block external dimension L	34.4 mm
Number of Block Mounting	4

4SRS12M+[36-1000/1]LM Bearing 2D drawings and 3D CAD models



FGDB Pump Machinery Equipment Co., Ltd.

Holes(holes)	
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	3.2 mm
Block dimension L1	20.6 mm